



Internet Camera for Home/SOHO Security

With Integrated Web Server & Motion Detection

The DCS-900 Internet camera is designed as a cost-effective security system for home and the small office. This camera connects to an Ethernet network in a building, or to the broadband Internet. Equipped with a built-in Web server and software for multi-camera monitoring and management, this camera provides a complete system for effective surveillance from a local site or anywhere via the Internet.

Stand-alone System With Integrated Web Server

This Internet camera comes with a built-in CPU and Web server, providing a low-cost solution capable of solving demanding security and home/office monitoring needs. Its integrated Web server eliminates the need to connect the camera to a computer. Once installed, you use the built-in IP address to gain access to the camera, make changes to camera settings, and view live video.

Web-based Remote Access

For remote security monitoring, you can install your camera at your home or the office, then view the images from anywhere via a computer running Internet Explorer or Netscape. Directly connected to the Internet without going through any computer, this camera is simple to install and can easily integrate with your network environment.

Motion Detected Recording

Instead of recording 24 hours a day, 7 days a week, images can also be recorded only when motions are detected. This

saves your disk space and eliminates the time wasted to view unnecessary images. Images can be directly archived straight to your computer hard drive or to a Network Attached Storage.

Multi-Camera Monitoring

Surveillance software, called "IPView Lite", is included to let you view up to 4 cameras on a single computer screen at one central location. Images can be recorded to your computer's hard drive manually or according to a pre-set schedule.

High-Quality Video

The DCS-900 supports video resolutions at up to 640 x 480 dpi. The camera uses M-JPEG to stream live video at up to 30 frames per second for real-time viewing.

Key Features

- Stand-alone Internet camera with CPU & RAM, no need to attach to PC
- Simple to use with real-time monitoring
- Local access through Ethernet
- Remote access from web browser
- Operates in Windows and Mac environments
- Surveillance software to control up to 4 cameras
- Motion detection triggered recording or scheduled recording
- Motion JPEG data compression ratio recording
- Implemented for intruder detection with still image capture (snap-shots) & e-mail notice
- Powerful software for image capture & video recording
- Scheduled recording for each camera
- Web-based configuration
- Windows-based Setup Wizard supporting Win98, XP, 2000, ME

DCS-900

Technical Specifications

Internet Camera

Camera Specifications

- 24-bit RGB, 640 x 480 resolution
- 1/3" color CMOS sensor, interlace scan mode
- Operating System: RTOS (real-time O.S.)
- Automatic Gain control (AGC) support
- Automatic Exposure (AE) support
- Automatic white balance support
- Signal/noise ratio: 56dB
- Lens mounting: fixed lens

Image (Video Setting)

- Motion
- JPEG compression
- Compression ratio: 5 levels
- Maximum image frame rate: 30fps
- Adjustable image size, quality and bit-rate
- Time stamp and text overlay

Communication

- RJ-45 auto-sensing port to connect to 10/100Mbps Ethernet
- Supported communication protocols: HTTP, FTP, SMTP, DHCP, NTP, DNS

System Requirement (for Viewing)

- Internet Explorer 5.x or above
- Netscape 6.0 or above

Security

- Administrator and user group protection
- 8-digit password authentication

Led Indicators

- Power
- Activity

Management and Software Update

- Configuration and system log access via Web browser
- Firmware upgrade via TCP/IP

Physical & Environmental

AC Adapter Power Input

100 to 240 VAC, 50/60Hz

DC Input

5V / 2.5A

Through external power adapter

Operation Temperature

5° to 50 °C

Storage Temperature

-25° to 50 °C

Humidity

5% to 95% non-condensing

Emission (EMI) & Safety Certifications:

- FCC Class B
- CE Class B
- LVD (EN60950)



Ordering Information

DCS-900 Internet Camera

Please specify your order as follows:

DCS-900A With US standard power adapter
DCS-900B With UK standard power adapter
DCS-900E With EU standard power adapter
DCS-900N With Australia standard power adapter

D-Link®

Specifications subject to change without prior notice.
D-Link is a registered trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

U.S.A	TEL: 1-949-788-0805	FAX: 1-949-753-7033
Canada	TEL: 1-905-8295033	FAX: 1-905-8295095
Europe	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511
Germany	TEL: 49-6196-77990	FAX: 49-6196-7799300
France	TEL: 33-1-30238688	FAX: 33-1-30238689
Benelux	TEL: 31-10-282-1445	FAX: 31-10-282-1331
Italy	TEL: 39-2-2900-0676	FAX: 39-2-2900-1723
Iberia	TEL: 34-93-4090770	FAX: 34-93-4910795
Sweden	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901
Norway	TEL: 47-22-309075	FAX: 47-22-309085
Denmark	TEL: 45-43-969040	FAX: 45-43-424347
Finland	TEL: 358-9-2707-5080	FAX: 358-9-2707-5081
Singapore	TEL: 65-6774-6233	FAX: 65-6774-6322
Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
Japan	TEL: 81-3-5434-9678	FAX: 81-3-5434-9868
China	TEL: 86-10-8518-2533	FAX: 86-10-8518-2250
India	TEL: 91-22-652-6696	FAX: 91-22-652-8914
Middle East	TEL: 9714-8834234	FAX: 9714-8834394
Turkey	TEL: 90-212-335-2553	FAX: 90-212-335-2500
Chile	TEL: 56-2-232-3185	FAX: 56-2-232-0923
Brasil	TEL: 55-11-3094-2910	FAX: 55-11-3094-2921
South Africa	TEL: 27(0)1266-52165	FAX: 27(0)1266-52186
Russia	TEL: 7-095-737-3389	FAX: 7-095-737-3390
Taiwan	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515
D-Link Corp.	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299



RECYCLABLE
Rev. 01 (Oct. 2003)