

# **DCS-F1614**

### **4MP Fixed Dome HD** Camera



### **KEY FEATURES**

- Full HD 4MP
- IR Range up to 20m
- Fixed Lens: 3.6mm
- Support AHO /T VI / CVI / CVBS Output (OSD)
- Video Transmission 300m
- 1/3" Scan CMOS
- 2D DNR, dWDR, ICR, Mirror, ATW, BLC, UTC
- 12V DC Power
- IP66
















## DCS-F1614 4MP Fixed Dome HD Camera

### **DIMENSION**



#### **ACCESSORIES**





#### **SPECIFICATION**

SPECIFICATION	
CAMERA	
Image Sensor	1/3"CMOS
Signal System	PAL/NTSC
Min. illumination	Color: 0.01Lux (F1.2, AGC ON); B/W: 0 Lux @ (IR LED ON)
S/N Ratio	≥48dB
Day & Night	ICR (Auto, Color, B/W, Ext)
Shutter Speed	PAL: 1/25s-1/10000s; NTSC:1/30s-1/10000s
Wide Dynamic Range	dWDR
Digital Noise Reduction	Auto/Manual (1-10)
Lens	3.6mm
FOV	85°
IR LED	18pcs
IR Wavelength	850nm
Ir Range	20m
OSD	Supported
IMAGE	
Effective Resolution	2560 x 1440
Frame	PAL: 25fps, NTSC:30fps
VIDEO OUTPUT	
Max Distance	75-5 300m
Video Output	AHD/TVI/CVI/CVBS
GENERAL	
Power Supply	DC12V±10%
Power Consumption	3.5W (Max)
Operating Temperature	-10°C~55° (14°F~131°F)
Operating Humidity	0% - 85% RH
Ingress Protection	IP66
Approvals	CE/FCC
Material	Aluminium Alloy
Product Dimensions	ø94 x 84mm
Product Weight	360g

