

DCS-F1615

5MP Fixed Dome HD Camera



KEY FEATURES

- Full HD 5MP/4MP
- IR Range up to 20m
- Fixed Lens: 3.6mm
- Support AHO /T VI / CVI / CVBS Output (OSD)
- Video Transmission 300m
- 1/2.5" CMOS
- 2D DNR, dWDR, ICR, Mirror, ATW, BLC, UTC
- 12V DC Power
- IP66

















DCS-F1615 5MP Fixed Dome HD Camera

DIMENSION



ACCESSORIES





SPECIFICATION

JI LCII ICATION	
CAMERA	
Image Sensor	1/2.5" CMOS
Signal System	PAL/NTSC
Min. illumination	Color:0.001Lux@(F1.2,AGC ON); B/W: 0 Lux@(IR LED ON)
S/N Ratio	≥50dB (min) (AGC closed)
Day & Night	ICR (Auto, Color, B/W, Ext)
Shutter Speed	PAL:1/25s-1/10000s; NTSC:1/30s-1/10000s
Wide Dynamic Range	dWDR
Digital Noise Reduction	Auto/Manual (1-10)
Lens	3.6mm
FOV	85°
IR LED	18pcs
IR Wavelength	850nm
Ir Range	Up to 20m
OSD Joystick	Support
Up the Coax	Only AHD Support
IMAGE	
Effective Resolution	2560x1920
Frame	20fps
White Balance	ATW/MWB
Mirror	Support
VIDEO OUTPUT	
Max Distance	75-5 300m
Video Output	AHD/TVI:5MP, AHD/CVI/TVI:4MP, CVBS
GENERAL	
Power Supply	DC12V±10%
Power Consumption	3.5W (Max)
Operating Temperature	-10°C ~ 55°C (14°F ~ 131°F)
Operating Humidity	0% - 85% RH
Ingress Protection	IP66
Approvals	CE/FCC
Material	Aluminium Alloy
Product Dimensions	ø94 x 84mm
Product Weight	360g

