



DFE-530TX+

- Easy Installation
- Updated Drivers for Mac OS X 10.1 & Win XP
- Wake-On-LAN Management Support
- Boot ROM Socket
- Limited Lifetime Warranty

Express EtherNetwork™ 10/100Mbps Fast Ethernet PCI Adapter



The D-Link DFE-530TX+ is a 10/100Mbps Fast Ethernet 32bit PCI Adapter for desktops, workstations, and servers. The DFE-530TX+ supports a wide range of operating systems including Macintosh and Windows.

With support for IEEE802.3 and IEEE 802.3u standards, the DFE-530TX+ supports 10BASE-T and 100BASE-TX networks. The DFE-530TX+ utilizes auto-negotiation to automatically adjust to the highest supported transfer rates up to 200Mbps in full duplex mode.

D-Link's DFE-530TX+ also supports optional advanced networking support

features like Wake-On-LAN and Boot ROM. Computers and operating systems that support the Advanced Configuration and Power Interface (ACPI) can remotely wake your PC from anywhere on the network with Wake-On-LAN. With the addition of an optional Boot ROM with PXE support, the DFE-530TX+ can support network booting of supported operating systems.

The DFE-530TX+ is a cost effective and versatile solution for a wide range of desktop connectivity environments.

Express EtherNetwork™

10/100Mbps Fast Ethernet

PCI Adapter



DFE-530TX+

SPECIFICATIONS

Features

- PCI Local Bus Master 2.1/2.2 Support
- Plug-and-Play installation
- Supports 20/200Mbps in Full Duplex Mode
- Supports 10/100Mbps in Half Duplex Mode
- Supports PCI 2.1/2.2 ACPI Power Management Wake-On-LAN (Magic Packet, LinkChg and Microsoft wake-up frame) Compliant to PC 99 Standard
- Independent 2Kbyte receive and transmit FIFOs

Drivers Supported

- Windows XP/Me/2000/98SE/98/95/NT 4.0
- Apple Macintosh 9.x or 10.1x
- NDIS 2.0 for Microsoft LAN Manager for DOS
- NDIS 2.0 for Microsoft Network Client 3.0 for Workgroup 3.11
- Packet Driver
- Novell Netware DOS ODI Driver
- Novell Netware Server v3.12, v4.1x and v5.0
- Linux

Standards

- IEEE 802.3 10Base-T Ethernet
- IEEE 802.3u 100Base-TX FastEthernet
- ANSI/IEEE 802.3 NWay Auto-Negotiation
- IEEE 802.3x Full Duplex Flow Control Support

Network Media

Ethernet: UTP Cat3, 4, 5 EIA/TIA-568 100-ohm screened twisted-pair (STP)
Fast Ethernet: UTP Cat5, EIA/TIA-568 100-ohm screened twisted-pair (STP)

Diagnostic LEDs

Link: LED indicator lit when there is an active Ethernet link
Activity: LED indicators blink whenever there is a reception or transmission of a frame

Protocol

- CSMA/CD

MTBF

- 176330 hrs

Network Data Transfer Rate

Ethernet: 10Mbps (Half-duplex)
Ethernet: 20 Mbps (Full-duplex)
Fast Ethernet: 100Mbps (Half-duplex)
Fast Ethernet: 200Mbps (Full-duplex)

Temperature

Operating: -10° to 55°C
Storage: -10° to 70°C

Humidity

Operating: 10% to 90% RH NC
Storage: 5% to 90% RG NC

Compliances

- CE Class B, FCC Class B, VCCI-B

Warranty

- Limited Lifetime

The D-Link DFE-530TX+ is a multi-platform 10/100BASE-T PCI Ethernet adapter for desktop computers. This high performance, 32-bit adapter is automatically detected by the computer's operating system and delivers up to 200Mbps throughput.

Product Information

Part No: DFE-530TX+

Description: Fast Ethernet PCI Adapter

UPC: 790069-220333

D-Link Systems, Inc.

TEL: (800) 326-1688

www.dlink.com

Package Contents

- DFE-530TX+ Fast Ethernet PCI Adapter
- Drivers & Manual on CD-ROM
- Installation Guide
- Wake-On-LAN Cable
- Standard & Low Profile Brackets



D-Link Systems, Inc. 53 Discovery Drive Irvine CA 92618 www.dlink.com

©Copyright D-Link Systems, Inc. 2002. All rights reserved. D-Link® is a registered trademark of D-Link Systems, Inc. Other trademarks or registered trademarks are the property of their respective manufacturers or owners. Price and specifications are subject to changes without notice. See inside package for warranty details.

* 24/7 Tech Support is available only in USA.

D-Link®
Building Networks for People